

J Mac

JME20 QUOTATION SHEET

MODEL	DESCRIPTION
JME20	Boom deflexion; Closed Cabin; Rubber track; Bucket width 400mm, 0.06m3, Heater&fan; Hammer pipes; Kubota D1105 Euro5/ EPA4 engine.

Picture



Options:

Extension track	£1090	Kubota D1105 Euro5/ EPA4 engine	£included
Without Closed Cabin	-£700	Hydraulic quick hitch	£520
Mechanical quick hitch	£310		

Attachments:

260mm narrow bucket		£125	Rake		£125
---------------------	---	------	------	---	------

800mm cleaning bucket		£210	Auger		£1150
800mm tilting bucket		£795	Ripper		£170
Grapple		£380	Hammer		£1150

Specifications:

Engine

Model	Kubota D1105 Euro5/ EPA4 engine	

Main Performance

Swing Speed	r/min	10-12
Traveling Speed	km/H	2.8
Grade ability	%	70(35°)
Traveling Tracking Force	kN	15
Bucket Digging Force	kN	11.5
Arm Digging Force	kN	9.3

Hydraulic System

Hydraulic system working pressure	Mpa	16
Hydraulic Pump	Gear Pump	AHWY
Hydraulic pump flow	L/min	22×2+8.8
Swing Motor		Eaton
Traveling Motor		Eaton

Fuel Tank Capacity	L	26
Hydraulic Tank Capacity	L	27

Overall Dimensions

Overall Length	mm	3800
Overall Width	mm	1050
Overall Height	mm	2280
Ground clearance	mm	485
Track length	mm	1630
Track width	mm	230
Undercarriage width	mm	1050
Undercarriage ground clearance	mm	235

Operation parameters

Operation Weight	KG	1800
Bucket Capacity	m ³	0.06
Max. Digging Radius	mm	3860
Max. Digging Depth	mm	2050
Max. Digging Height	mm	3370
Max. Dumping Height	mm	2390
Max. Dozer Cutting	mm	270
Max. Dozer Lifting	mm	235
Boom Deflexion (Left/Right)	°	75/45

J Mac Excavators Ltd, Whitehouse Farm, Malthouse Lane, Earlswood, Solihull, Warwickshire,
United Kingdom B94 5DX

T. +44 (0)1564 336633 E. sales@jmacuk.com www.jmacuk.com
Company registered in England & Wales, Number 11291171